



## SAFE COMMUNICATIONS IN EXTREME ENVIRONMENTS

### KEY FEATURES

Only multiband portable meeting UL's C1D1 standards for intrinsic safety

Robust connectivity with VHF, UHF and 700/800 frequency capabilities

Rugged and compact to withstand extreme conditions

Advanced noise cancellation delivers loud and clear audio

Multiple encryption options including single-key AES standard

# XL-200Pi

## INTRINSICALLY SAFE MULTIBAND LAND MOBILE RADIO

The Harris XL-200Pi is today's only multiband portable meeting Underwriter Laboratories' (UL) Class 1, Division 1 (C1D1) standards for intrinsic safety in potentially explosive, hazardous environments. Fire departments, utilities, mining, hazmat responders and oil and gas workers now have a safe and ruggedized communications solution to rely on for critical communications during extreme conditions.

Designed with input from first responders, the XL-200Pi delivers advanced connectivity with robust LMR voice and data over VHF, UHF and 700/800 frequencies. Wi-Fi®, Bluetooth® and GPS are included as standard.

This intrinsically safe portable is designed to protect against water and dust penetration. Compact and ergonomic, the XL-200Pi fits naturally into users' hands, with controls shaped for fast, easy gloved hand operation.

Engineered for audio excellence with a 1.5 watt/4.0 watt max amplifier with woofer and tweeter speakers, the XL-200Pi has the latest noise cancellation technologies that suppress acoustic feedback and provide clear communications through a wide range of conditions.

The XL-200Pi supports multiple encryption options including single-key AES encryption for secure communications.

SPECIFICATIONS FOR: XL-200Pi-INTRINSICALLY SAFE LAND MOBILE RADIO

**GENERAL**

<b>Radio Models:</b>	TFT LCD w/DTMF keypad, navigation cluster, soft keys	
Full Keypad	TFT LCD w/partial keypad, navigation cluster, soft keys	
Partial Keypad		
<b>Dimensions w/Battery (H x W x D)</b>	5.8 x 2.3 x 1.6 in (148.0 x 60.0 x 42.0 mm)	
<b>Weight</b>	17.9 oz (507 g) w/Battery and Antenna	10.4 oz (296 g) w/o Battery and Antenna
<b>Housing Colors</b>	Midnight Black, High-Visibility Yellow	
<b>Interfaces:</b>		
Front Display	320 x 178 pixels, 1.8 inch transfective LCD, 16-bit color with backlight	
Top Display	128 x 32 pixels, 1.1 inch multi-color backlight, sunlight readable	
Keypad	Backlight, 3 soft keys, 5-way navigation key, full DTMF keypad	
Buttons	Large PTT button, on/off knob, volume knob, red emergency button, 16-position top-mounted rotary knob, 2-position concentric switch, 4-position toggle switch, 3 programmable side buttons	
Tx/Rx Indicator	Multi-colored LEDs	
<b>Transceiver</b>	<b>Supported Bands</b> VHF, UHF, 700/800 MHz	<b>Channel Capacity</b> 12,500 (1,250 per mission plan)
<b>Environmental:</b>		
Relative Humidity	5% @ 140° F (+60° C), 95% @ 122° F (+50° C)	
Vibration	USDA LMR Standard, Section 2.15 and MIL-STD-810G, Test Method 514.6	
Drop Shock	1.0 meter drop to concrete (exceeds TIA-603-D)	
Immersion <sup>1</sup>	2 meters for 4 hours in accordance with MIL-STD-810G/IP68	
<b>Operating Temperature<sup>2</sup></b>	-22° F to +140° F (-30° C to +60° C)	
<b>Storage Temperature<sup>3</sup></b>	-40° F to +176° F (-40° C to +80° C)	
<b>Altitude</b>	<b>Operational</b> 15,000 feet (4,572 meters)	<b>In Transit</b> 50,000 feet (15,240 meters)
<b>Electrical Input Voltage</b>	7.5 VDC (nominal)	
<b>GPS/GNSS Specifications:</b>		
Channels	52	
Tracking Sensitivity (dBm)	-166 (GPS), -163 (GLONASS)	
Acquisition Sensitivity (dBm)	-146 (GPS)	
Cold Start w/-130 dBm input	<35 seconds	
Hot Start w/-130 dBm input	<1 second	
<b>Safety:</b>		
Hazardous Location Options	U.S.: Class 1, Division 1, Groups C and D; Class II, Division 1, Groups E, F and G; Class III, Division 1 hazardous locations; Class 1, Division 2, Groups A, B, C and D	
RoHS Compliant	Canada: Class 1, Division 2, Groups A, B, C and D hazardous locations	

<sup>1</sup> Optional feature

<sup>2</sup> Extreme low temperatures adversely affect battery life

<sup>3</sup> Store batteries at +25° C ± 5° C

**LMR TRANSMITTER**

Frequency Bands	VHF*	UHF*	700/800 MHz
<b>Frequency Ranges (MHz)</b>			
Option 1 (U.S.)	136-174	378-522	768-776, 798-806, 806-816, 851-861
Option 2 (International/Non-rebanded)	136-174	378-522	763-776, 793-806, 806-825, 851-870
<b>Rated RF Power/Talkaround (W)</b>	1-6	1-5	0.5-3
<b>Frequency Stability (-30 to +60°C)</b>	±1.0 ppm	±1.0 ppm	±1.0 ppm
<b>Modulation Limiting (kHz)</b>	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)
<b>Audio Response (dB)</b>	+1/-3	+1/-3	+1/-3
<b>Spurious and Harmonics (dBc)</b>	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)
<b>FM Hum and Noise Companion Receiver (dB):</b>			
@ 25 kHz	70	60	55
@ 12.5 kHz	47	47	45
<b>Audio Distortion (%)</b>	<1.25	<1.25	<1.25
<b>Project 25 Modulation Fidelity (%)</b>	1.0	1.0	1.0
<b>Project 25 Adjacent Channel Power (dBc)</b>	>71	>71	>71

\*Full-spectrum multiband VHF and UHF product is compliant with applicable FCC narrowbanding mandate below 512 MHz

**REGULATORY DATA**

Frequency Range	RF Output	Frequency Stability	FCC Type Acceptance No.	Applicable FCC Rules	Industry Canada Certification No.	Applicable Industry Canada Rules	NTIA Cert. No.
136-174 MHz	6 W	±1.0 ppm	OWDTR-0144-E, OWDTR-0146-E	22, 74, 80, 90	3636B-0144, 3636B-0146	RSS-119	SPS-217 49/1
378-522 MHz	5 W	±1.0 ppm	OWDTR-0144-E, OWDTR-0146-E	22, 74, 80, 90	3636B-0144, 3636B-0146	RSS-119	SPS-217 49/1
768-776 MHz	3 W	±1.0 ppm	OWDTR-0144-E, OWDTR-0146-E	90	3636B-0144, 3636B-0146	RSS-119	
798-806 MHz	3 W	±1.0 ppm	OWDTR-0144-E, OWDTR-0146-E	90	3636B-0144, 3636B-0146	RSS-119	
806-816 MHz	3 W	±1.0 ppm	OWDTR-0144-E	90	3636B-0144	RSS-119	
806-825 MHz	3 W	±1.0 ppm	OWDTR-0146-E	90	3636B-0146	RSS-119	
851-861 MHz	3 W	±1.0 ppm	OWDTR-0144-E	90	3636B-0144	RSS-119	
851-869 MHz	3 W	±1.0 ppm	OWDTR-0146-E	90	3636B-0144	RSS-119	

SPECIFICATIONS FOR: XL-200Pi-INTRINSICALLY SAFE LAND MOBILE RADIO

REGULATORY DATA (Continued)							
Frequency Range (MHz)	RF Output (W)	Frequency Stability	FCC Type Acceptance No.	Applicable FCC Rules	Industry Canada Certification No.	Applicable Industry Canada Rules	NTIA Cert. No.
2402-2480	0.2	NA	OWDTR-0144-E, OWDTR-0146-E	15	3636B-0144, 3636B-0146	RSS-119	
5180-5825	0.1	NA	OWDTR-0144-E, OWDTR-0146-E	15	3636B-0144, 3636B-0146	RSS-119	

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

LMR RECEIVER			
Frequency Bands	VHF	UHF	700/800 MHz
<b>Frequency Ranges (MHz):</b>			
Option 1 (U.S.)	136-174	378-522	768-776, 851-861
Option 2 (International)	136-174	378-522	763-776, 851-870
<b>Channel Spacing (kHz)</b>	25 (wideband*), 12.5 (narrowband), 6.25 equiv (TDMA P25 Phase 2)		
<b>Frequency Stability (-30 to +60°C)</b>	±1.0 ppm	±1.0 ppm	±1.0 ppm
<b>Sensitivity (dBm):</b>			
@ 12 dB SINAD	-122	-121	-121 (700 MHz) -120 (800 MHz)
<b>Project 25 Reference Sensitivity (dBm):</b>			
@ 5% BER	-122	-121	-120.5
<b>Analog Selectivity (dB):</b>			
@ 25 kHz	77	77	74
@ 12.5 kHz	71	70	64
<b>Project 25 Adjacent Channel Rejection (dB)</b>	66.2	62.2	62
<b>Offset Channel Selectivity (dB):</b>			
@ NPSPAC	NA	NA	30
<b>Intermodulation (dB)</b>	80	81	77
<b>Spurious and Image Rejection (dB)</b>	90	87	80
<b>FM Hum and Noise (dB):</b>			
@ 25 kHz	-60	-60	-55
@ 12.5 kHz	-55	-53	-50
<b>Audio Output - Rated/Max (mW)</b>	1500/4000	1500/4000	1500/4000
<b>Audio Distortion @ Rated Power (%)</b>	1.1	1.1	1.1

\*Full-spectrum multiband VHF and UHF product is compliant with applicable FCC narrowbanding mandate below 512 MHz

ENVIRONMENTAL STANDARD			
Applicable MIL-STD	Parameter	Methods	Procedure/Categories
MIL-STD-810G*	Low pressure	500.5	1, 2
	High temperature	501.5	1, 2
	Low temperature	502.5	1, 2
	Temperature shock	503.5	1
	Solar radiation	505.5	1
	Contamination by fluids	504.1	2
	Rain	506.5	1, 3
	Humidity	507.5	2
	Salt fog	509.5	1
	Blowing dust and sand	510.5	1, 2
	Explosive atmosphere	511.5	1
	Immersion in water**	512.5	1
	Vibration (minimum integrity)	514.6	1, Category 24
	Vibration (basic transportation)	514.6	1, Category 4
	Shock (functional/basic)	516.6	1
	Shock (transit drop)	516.6	4
	Shock (bench handling)	516.6	6
IEC 60529	Dust-tight, continuous immersion in water**		IP68

\*Also meets equivalent superseded MIL-STD-810D, -E and -F

\*\*Optional feature

BROADBAND	
Wi-Fi	802.11 b/g/n 2.4 GHz and 5 GHz
Bluetooth	Bluetooth 4.0 (128-bit encryption)

## SPECIFICATIONS FOR: XL-200Pi-INTRINSICALLY SAFE LAND MOBILE RADIO

### DIGITAL OPERATION

Protocol	ProVoice™	P25
Vocoding Method	AMBE +2™ enhanced full rate	AMBE +2 enhanced full rate and enhanced half rate
Signaling Rate (kbps)	9.6	9.6
Modulation	GFSK	Phase 1 Tx: C4FM, Rx: C4FM and WCQPSK

### ENCRYPTION

Encryption Algorithms	Voice Encryption: Single-key AES/DES, Multiple-key AES/DES, DES-OFB, Encryption Lite (ARC4), 256-bit AES P25, 64-bit DES Control Channel Encryption: 128-bit AES (LLA)	
Encryption Keys per Radio	Capable of storing 128 keys (64 AES, 64 DES)	
Keying	Harris Key Loader, Over-the-Air Rekeying (OTAR), Motorola KVL 3000+/4000	
Standards	FIPS 140-2, FIPS 197	

### BATTERIES

Type	Dimensions (H x W x D)	Weight	Capacity (mAh)
Li-Ion	3.0 x 2.3 x 1.1 in	6.1 oz (174 g)	3300

### ACCESSORIES

The XL-200Pi is available with a selection of dependable C1D1-rated Harris accessories that operate in a range of environments. Several are shown below.

#### Chargers

Harris offers a variety of chargers for the XL-200Pi: Single-Bay, Multi-Bay and a Vehicular Charger for in-car charging. The chargers are designed to quickly and safely charge battery packs in approximately 1 to 4 hours.



Single-Bay Charger



Multi-Bay Charger



Vehicular Charger

#### Additional Accessories Available

Standard speaker microphones, earphones for standard speaker microphones, belt clip, Lithium Ion battery, PC programming software and cables and antennas.

Technical specifications are subject to change without notice. Product sales are subject to applicable U.S. export control laws.

#### About Harris Corporation

Harris Corporation is a leading technology innovator, solving customers' toughest mission-critical challenges by providing solutions that connect, inform and protect. Harris supports government and commercial customers around the world. Learn more at [harris.com](http://harris.com).

FLORIDA | NEW YORK | VIRGINIA | BRAZIL | UNITED KINGDOM | UAE | SINGAPORE

#### Non-Export Controlled Information

Harris is a registered trademark of Harris Corporation. Trademarks and trade names are the property of their respective companies.

© 2017 Harris Corporation 09/17 CS-PSPC DS1906

**HARRIS**® TECHNOLOGY TO CONNECT,  
INFORM AND PROTECT™